

| REVISION RECORD | | | |
|-----------------|---------|------|------|
| REV. | CONTENT | MOD. | DATE |
| △ | 初版发行 | | |

NOTES1:

UL Standard:

1.Voltage Rating: 300V, Current Rating: 10A

NOTES2:

1.Pitch : 5.08mm

2.Withstand Voltage : AC2500V for 1 minute

3.Using Temperature Range : - 40℃ ~ + 105℃

4.Suitable Electric Wire: 26-12AWG

技术要求1:

UL 标准:

1. 额定电压: 300V, 额定电流: 10A

技术要求2:



1. 间距: 5.08mm

2. 耐电压值: AC2500V/min

3. 使用条件: -40℃~+105℃

4. 适用线规: 26~12AWG

| 6 | LZ1-耳朵螺母 | SM00B25000V | 2 | 黄铜 | |
|---|----------------|--------------|------------|----------|------------------------|
| 5 | LC60-5.08五金件 | 2083B0001AV | P | 磷青铜 | 镀锡 |
| 4 | LC6-5.08-弹片 | F2A0DLC658BV | P | 不锈钢 | |
| 3 | LC6-5.08-按钮 | 1020D0Y01AV | P | POM | |
| 2 | LC60MG-5.08-盖板 | 2083N0YXXAV | 1 | PA66-V0 | |
| 1 | LC6-5.08-本体 | 1020A0YXXAV | 1 | PA66-V0 | |
| NO. | NAME OF PART | NO. OF PART | Q' TY | MATERIAL | NOTES |
| DES. | CMZ | DATE | 2025/03/26 | UNITS | MM |
| CHK. | | DATE | | SIZE | A4 |
| APP. | | DATE | | SCALE | 1:1 |
| | | | | DWG NO. | SP-2-208302 |
| | | | | REV: | V0 |
|  上海有乐电气有限公司 Shanghai YouLe Electric Co., LTD | | | | TITLE | LC60MG-5.08-XXP-1Y-00A |
| | | | | | LC60MG-5.08-成品 |

| | pitch dimension | | | Nominal dimension | | | | | — / |
|----------------|-----------------|-------|-------|-------------------|------|------|------|------|---|
| | over | over | over | over | over | over | over | over | |
| variable range | 0 | 6 | 10 | 0 | 30 | 60 | 100 | 150 |  |
| | to | to | to | to | to | to | to | |  |
| | 6 | 10 | 24 | 30 | 60 | 100 | 150 | | |
| Tolerance | ±0.1 | ±0.15 | ±0.25 | ±0.2 | ±0.3 | ±0.5 | ±0.7 | ±1.0 | 0.05/10 |